

VISION H-GLOSS POLISH

Physical Properties

Appearance:White opaque liquid
Solids Content22% RI Solids
Coverage:30-60m² per litre/coat
Fragrance:No fragrance
pH:9.0 (100%)

Recoat.....30 minutes

Finish: Gloss

Packaging: .5lt Containers

PRODUCT DESCRIPTION

Vision H-Gloss Polish is a metal cross-linked floor polish. It gives durability, superior wet look gloss finish and is easy to use. It flows evenly and levels quickly to dry to a lustrous gloss. Subsequent coats apply smoothly without drag, pulling, streaking or clouding. It resists surface scuffs, black heel marks and soil penetration, allowing extended periods between maintenance. Suitable for use where slip resistance is required. Expect a long wearing finish when used in high speed burnishing programs as well as in conventional maintenance programs.

The quick drying formula allows multiple coats to be applied in short periods of time. 1 litre does approximately one coat of 30-60m².

ADVANTAGES

- Commercial strength
- Water Based
- High solid content
- Cost effective
- Great looking finish

DIRECTIONS

1. Vision H-Gloss should be applied to a clean floor prepared by stripping or scrubbing off the old finish if required (when the layers are too thick or the finish has dulled completely). We recommend using Vision Strip.
2. Using a clean finish mop or applicator, apply 3-4 coats of Vision H-Gloss in even, medium coats. Before recoating, allow each coat to dry (approximately 30 minutes). Increased gloss and durability can be achieved by additional coats.
3. Maintain finish by frequent dust mopping and wet cleaning with Vision Floor Cleaner.

COVERAGE

Approximately 30-60m² per litre/coat

NOTES

1. Do not polish around furniture. All furnishings should be removed out of the area and replaced once the Vision H-Gloss polish is dry.
2. We recommend felt pads be fitted to moveable furniture to prevent surface scratching..

DISCLAIMER

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control. As all Permacolour's technical data sheets are updated on a regular basis, it is the users responsibility to obtain the most recent issue.

CONDITIONS OF SALE: The material is guaranteed to be of standard quality and to conform to our published specifications. Since we have no control over use and application of this material, nor the areas to which it is applied, we disclaim any and all responsibility or warranties, expressed or implied, in connection with its' use, handling and storage or the results obtained; as well as any injury, damage of any nature whatsoever, resulting from its uses.

WARRANTY

Permacolour products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification.